

WXD 2020

2-Channel Solder- and Desoldering Station, 200 W (255 W)
Code No.: T0053429699N



Benefits

- › Soldering and desoldering station, 2 channels with WXDP 120 and soldering iron WXP 120
- › Soldering- and desoldering tools with intelligent WX technology
- › Connection to external compressed air supply for high vacuum
- › Energy effective: automatic stand-by mode for tools
- › Patented, ESD safe glass display. Simple and fast setting of soldering parameter.



In addition we recommend:



Fume extraction devices



Soldering Irons



Cleaning Consumables



Preheating plates



Technical Data

Dimensions W x D x H (mm)	174 x 154 x 135
Dimensions W x D x H (Inch)	6, 69 x 5, 94 x 5, 12
Weight (ca) in kg	3.8
Voltage	230 V, 50 Hz
Power output	200 W (255 W)
Channels	2
Temperature range (depends on tool) °C	---
Temperature range (depends on tool) °F	---
Temperature accuracy °C	±9
Temperature accuracy °F	±17
Temperature stability °C	±2
Temperature stability °F	±4
Equipotential bonding	Via 3,5 mm pawl socket on back of unit.
Display	255 x 128 dots / Backlighting
Air consumption l/min	35
Operating pressure	4,0 - 6,0 / 58 - 87
Capacity l/min	---
Vacuum	max. 55 kPa (8psi)

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE